



No installation limits and no joints required.
Dryback solution that will guarantee a long-term durability of your floor.

TEST	STANDARD	METROPOLITAN COLLECTION	SCANDINAVIAN COLLECTION	SPRING COLLECTION	BEACH COLLECTION	POWER COLLECTION
Category		Commercial Pro 25.55	Commercial Pro 25.55	Commercial Pro 25.55	Commercial Pro 25.55	Commercial Pro 25.70
Dimensions	EN 427 / EN 428	1219 x 229 x 2,5 mm	1219 x 229 x 2,5 mm	1524 x 229 x 2,5 mm 762 x 152 x 2,5 mm Herringbone	762 x 152 x 2,5 mm Herringbone	711 x 119 x 2,5 mm Chevron
Emboss / Surface		Regular Wood Semi-matte	Regular Wood Semi-matte	Realistic Wood Super-matte	Realistic Wood Semi-matte	Realistic Wood Semi-matte
Impact Sound Reduction	EN 140	5 dB	5 dB	5 dB	5 dB	5 dB
Suitable for	EN 16511	Residential / Commercial Very High	Residential / Commercial Very High	Residential / Commercial Very High	Residential / Commercial Very High	Residential / Commercial Very High
Weight	EN 430	4,78 kg/m ²	4,78 kg/m ²	4,59 kg/m ²	4,78 kg/m ²	4,78 kg/m ²
Fire Performance	EN 13501	Bfl - S1				
Abrasion Wear	EN 425	Pass Castor Chair (W)				
Dimensional Stability	EM 434	Approved				
Indentation	EN 433	max 0,08mm				
Chemical Resistance	EN 423	Class 0 - Good				
Anti-static Resistance	EM 1815	< 2kV				
Slippery Resistance	DIN 51133 EN 13893	Class R9 Class DS				
Underfloor Heating		Approved 27°C				
Thermal Resistance	EN 12524	0,036 m ² K/W				
Thermal Conductivity	EN 12667	10.076 w(m-K)				
Toxicity	EN 71	Non Toxic				
Emissions Value AgBB/Dibt low VOC (U-Sign)		Certified				
Resistance to Fading	ISO 105 B02 2014-09	6/8 Good				

